

DESCRIPTION

			VariUse 8.3
Surface			X PUR scuff-resistant surface
Backing			Combined closed cell foam system
Thickness	mm	EN ISO 24346	8,3
Top layer	mm	EN ISO 24340	2,2
Weight	g/m ²	EN ISO 23997	4900
Width	m	EN ISO 24341	2
Standard roll length	m	EN ISO 24341	15 ± 10%

CLASSIFICATION

Product specification		EN 14904	Vinyl indoor sports floor (category P1)
Impact sound insulation	dB	EN ISO 717-2	21
Thermal resistance	m ² K/W	EN 10456	0,08
Reaction to fire	-	EN 13501	Cfl-s1


SPORT PROPERTIES

Friction	-	EN 13036-4	80-110
Shock absorption	%	EN 14808	≥ 25 (P1)
Vertical deformation	mm	EN 14809	max. 2,0
Ball rebound	%	EN 12235	99
Specular gloss	%	EN 2813	≤ 30

TECHNICAL CHARACTERISTICS

Dimensional stability	max. %	EN ISO 23999	± 0,2
Indentation resistance	mm	EN 1516	max. 0,5
Resistance to rolling load	1500 N	EN 1569	no damage
Colour fastness	-	ISO 105 B02	6
Chemical resistance	-	EN ISO 26987	no change
Abrasion resistance	mg/1000 cycles	EN ISO 5470-1	< 250 / 1000 cycles

OTHERS



GRABOPLAST LTD.

H-9023 Győr, Fehérvári út. 16/b. Telefon: (+36) 96 506-100
 instagram.com/graboplast | facebook.com/graboplast
 www.grabo1905.com

